

产品信息/Product Information

• 规格: JJ1200-003	• Specification: JJ1200-003
• 材质: 生物降解低密度聚乙烯 (BPE)	• Material: Biodegradable low density PE (BPE)
• 描述: 吹塑级; 可在露天土壤环境完全生物降解; 无毒害, 无微塑料, 可回收利用;	• Description: Blow grade; Fully biodegradable in open-air soil environment; No toxicity, no microplastics, recyclable;
• 特性: 保质期2-3年, 高透明, 热封性好, 加工性优异	• Features: Shelf life of 2-3 years, High transparency, good heat sealing, and excellent processability
• 用途: 化妆品软管, 牙膏管, 包装膜、复合膜等。	• Usage: Cosmetic hoses, toothpaste tubes, packaging films, composite films, etc.
• 材料标识: BPE	• Material identification: BPE
• 外观: 颗粒状	• Appearance: Granular
• 颜色: 本色	• Color: Natural
• 填充物: 无	• Filler: None
• 符合规定: • 生物降解: 欧洲: BSI PAS 9017, ISO 17556 中国: GB/T 41010之GB/T 22047 • 食品接触: 美国: FDA21 CFR 177.1520 欧盟: (EU) No.10/2011及(EU) 2020/1245 • 环保: Rohs、SVHC	• Compliant with regulations: • Biodegradation: Europe: BSI PAS 9017, ISO 17556 China: GB/T 41010 to GB/T 22047 • Food contact: USA: FDA 21 CFR 177.1520 EU: (EU) No.10/2011 and (EU) 2020/1245 • Environmental protection: Rohs, SVHC

物性表 datasheet

项目 Project	方法method	单位unit	JJ1200-003
熔融指数 Melt Index(190°C/2.16kg)	ISO 1133 -1	g/10min	0.35
密度 Density	ISO 1183 -2	g/cm3	0.920
拉伸强度 屈服 Tensile Strength Yield	ISO 527 -2	MPa	13
断裂延伸率 Tensile Elongation at Break	ISO 527 -2	%	500
雾度 Haze	ASTM D1003	%	13

** 因不能够预见到本产品可能被使用的所有情形, 对产品的安全性和适宜性, 除非另行书面约定, 恒昌泰不提供任何保证。购买者和使用者应自行承担因操作或使用我们的产品而产生的损失或损害的所有责任和义务。除非特别指明, 所提到的牌号不适用于药物/医疗范畴。Due to the unpredictability of all possible situations in which this product may be used, Hengchangtai does not provide any guarantees regarding the safety and suitability of the product unless otherwise agreed in writing. Buyers and users shall bear all responsibilities and obligations for losses or damages arising from the operation or use of our products. Unless otherwise specified, the mentioned brand does not apply to the drug/medical category.

对环境负责! 为未来选择!
Responsible for the environment! Choose for the future!